

3-Strip Longstrip

21 mm tongue/groove



Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	21 x 215 x 2200 mm
Toplayer:	about 5.5 mm
Construction:	3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 5.5 mm Middlelayer 10.5 mm Bottomlayer 5.0 mm
Boards/ m ² per carton:	4/ 1.89
Cartons/ m ² per pallet:	50/ 94.5
Slotted top layers per carton/ minimum length (mm):	1/ 600
Weight per carton/ pallet in kg:	21/ 1050
Floor heating systems:	Well suitable
Fire behavior ¹⁾ :	Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment
Content of formaldehyd ²⁾ :	E1
Content of pentachlorophenol (PCP) ²⁾ :	no performance detected
Density kg/ m ³ ²⁾ :	about 600
Antislip performance:	Live Satin USRV 25 ²⁾ Live Matt USRV 29 ²⁾ Live Natural USRV 40 ²⁾
Abrasion resistance:	Live Satin 70/ 1100 ³⁾ Live Satin 100 ⁴⁾ Sport lacquer T79: Coefficient of friction: 80-110 ⁴⁾ Dynamic coefficient of friction: 0.4-0.6 ⁷⁾
Thermal conductivity ²⁾ :	0.15 W/ (m·K)
Areal thermal resistance ³⁾ :	0.14 m ² · K/ W



DOP 4658



www.blauer-engel.de/uz176

CE
BOEN AS
 EN 14342



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696,

⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524